

cushion






Outsole

- SRA slip resistance according to EN ISO 20347
- Air cushion PU-sole shock absorption
- Extrem light sole

Insole

- replaceable insole (art. 3551), more information on page 122



Infobox

- low shoe
- ESD
- FITTING - narrow-normal
- Available from size 35 - 47
- Lining microfibre, breathable, moisture absorbing



Technology

- Antistatic/ESD dissipative according to EN 61340-4-3 and EN 61340-5-1



Perforation
for good ventilation



02 2700 **02**  32700



02 2710 **02**  32710

CE, EN ISO 20347 02, SRA

- size 39-47 • grained leather white, black • lining microfibre, breathable, moisture absorbing
- replaceable insole (art. 3551) • slip-resistant PU outsole



02 2610 **02**  32610



02 2600 **02**  32600

CE, EN ISO 20347 02, SRA

- size 35-47 • grained leather black, white • lining microfibre, breathable, moisture absorbing • replaceable insole (art. 3551)
- slip-resistant PU outsole



01 2370 **01**  32370

CE, EN ISO 20347 01, SRA

- size 35-47 • microfibre white • instep area with elastic band • integrated footbed
- washable • slip-resistant PU outsole



 A[®] micro



01



32300 • size 35-47



01



32310 • size 39-47

CE, EN ISO 20347 01, SRA

- grained leather white, black, perforated
- lining microfibre, breathable, moisture absorbing
- replaceable insole (art. 3551)
- slip-resistant PU outsole

