

**Static Control**

**technoLASA**





## Outsole

- SRA slip resistance according to EN ISO 20345
- Rubber outsole maximum grip
- Torsions waist hard rubber compound
- Protection from ankle twisting
- Resistant to fuel

## Insole

- replaceable acc Wave insole (art. 3553), more information on page 122



## Infobox

- low shoe
- ESD
- FITTING - normal
- Available from size 35 - 47
- Composite toe-cap (200 joules)
- metal free
- Soft PU midsole



## Technology

- Antistatic/ESD dissipative according to EN 61340-4-3 and EN 61340-5-1



**S1**  **1275**

**CE, EN ISO 20345 S1, SRA**

- size 36-47 • leather black with scratch-resistant carbon coating and **breathable textile inlays** • lining with silver ions • double velcro fastening • replaceable acc Wave insole (art. 3553) • slip-resistant special rubber outsole



**S1**  **31378**

**CE, EN ISO 20345 S1, SRA**

- size 36-47 • velour anthracite with **breathable textile inlays** • lining with silver ions • double velcro fastening • replaceable acc Wave insole (art. 3553) • slip-resistant special rubber outsole



**S2**  **31392**

**CE, EN ISO 20345 S2, SRA**

- size 36-47 • microfibre white • lining with silver ions • instep area with elastic band • replaceable acc Wave insole (art. 3553) • slip-resistant special rubber outsole



 **A<sup>micro</sup>**